



Product Data

Agri MP 15W-40

Universal tractor oil

Description

Castrol Agri MP is a universal oil for most types of farm machinery.

Advantages

- One oil that protects engine, transmission, wet brake, hydraulic and front axles.
- One oil reduces inventory, saves money.
- Using an advanced formulation, Castrol Agri MP reduces engine wear by up to 30% compared to conventional STOU products.

Typical Characteristics

Name	Method	Units	Agri MP 15W-40
Density @ 15C, Relative	ASTM D1298	g/ml	0.886
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.8
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	115
Viscosity Index	ASTM D2270	None	135
CCS @ -20°C	ASTM D5293	mPas	7000
Pour Point	ASTM D97	°C	-36
Sulphated Ash	ASTM D874	%wt	1.5
Flash Point, COC	ASTM D92	°C	200

Product Performance Claims

ACEA E2
API CF-4/SF/GL-4
Meets Ford M2C159B
JDM J27
MF M1139
ZF TE-ML 06B, 07B
May be used where M1144 is specified

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Agri MP 15W-40

20 Sep 2011

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa

+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)

www.castrol.co.za