



Aircol 99

Refrigeration compressor oil

Description

Aircol 99 is a refrigeration compressor lubricant formulated from highly refined naphthenic base oils for use in both large industrial and small domestic refrigeration units.

Application

Aircol 99 is formulated to function as a lubricant and coolant, as well as a sealant in refrigerating compressors. It maintains good lubrication properties at the high temperatures reached during the compression phase and good fluidity at the low temperatures within the evaporators. Excellent lubrication of the moving parts in the compressor as well as recycling of the oil, entrained into the system by the refrigerant, are therefore ensured.

The chemical stability of Aircol 99 prevents it from reacting with the refrigerants used in refrigeration systems to form potentially disruptive breakdown products. Aircol 99 is suitable for use in systems using Ammonia (NH₃) or halogenated hydrocarbons. It can also be used where good low temperature flow properties are required in the lubricant.

Features / Benefits

Aircol 99 oil ensures long and trouble-free operation of refrigeration systems through a combination of:

- High thermal and chemical stability.
- Good temperature / viscosity behaviour.
- Good low temperature flow properties.

Technical Data

Name	Method	Units	Aircol 99
Density @ 15C, Relative	ASTM D1298	g/ml	0.905
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	71.6
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.6
Viscosity Index	IP 226	None	53
Pour Point	ASTM D97	°C	-36
Flash Point, COC	ASTM D92	°C	192
Colour	ASTM D1500	-	1.5 - 2.0

The above figures are typical of those obtained with normal production tolerance, and do not constitute a specification.

Care and Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Packaging and Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60C, exposed to hot sun or freezing conditions.

Aircol 99
11 Jul 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrolmarine.com