



## Axle EPX 85W-140

Axle Fluid for specific OEMs

### Description

Castrol Axle EPX 85W-140 is a multipurpose axle oil which may be used in differentials, final drives and other applications in passenger cars and commercial vehicles where API GL-5 performance is required. It is approved by ZF for use in a range of commercial applications including axles in off-road and agricultural equipment.

### Advantages

- High load carrying capability ensures gears operating under high loads are protected prolonging component life.
- High film strength ensures protection against wear and shock loads.
- Good thermal/oxidation stability protects against the formation of deposits and oil thickening prolonging the life of components and lubricant.

### Typical Characteristics

Name	Method	Units	Axle EPX 85W-140
Density @ 20C, Relative	ASTM D4052	g/ml	0.904
Appearance	Visual	-	Clear & bright
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	24.5
Viscosity, Brookfield @ -12C	ASTM D2983	mPa.s (cP)	<150.000
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	405
Viscosity Index	ASTM D2270	None	95
Pour Point	ASTM D97	°C	-12

### Product Performance Claims

API GL-5  
ZF TE-ML 16D, 21A

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Axle EPX 85W-140

22 Sep 2011

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa  
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)  
[www.castrol.co.za](http://www.castrol.co.za)