



Castrol GTX Diesel 15W-40

Superior diesel engine protection

Description

Castrol GTX is one of the world's most trusted engine oils.

GTX Diesel is designed specially for today's automotive diesel engines. It's more than just oil. It's liquid engineering that fights diesel engine problems that your engine faces every day, like soot and harsh deposits. Why is this important? Because soot and harsh deposits can make the oil thicker; blocking oil ways, causing wear and decreasing performance. Castrol GTX Diesel is engineered to clean away and protect against harmful diesel engine deposits.

Application

Castrol GTX Diesel 15W-40 is suitable for use in automotive diesel engines including inter-cooled and turbo-charged engines where the manufacturer recommends an API CH-4 or earlier specification 15W-40 lubricant. It may also be used in gasoline engines where the manufacturer recommends an API SJ or earlier specifications.

Castrol GTX Diesel 15W-40 is approved for use in diesel vehicles manufactured by Tata Motors that require a 15W-40 lubricant.

Advantages

Castrol GTX Diesel provides superior protection for your diesel engine:

- Outstanding diesel engine wear protection
- Superior cleaning power to maintain engine performance
- Reduces build up of harsh deposits
- Helps prevent oil from thickening and keeps it flowing freely

Typical Characteristics

Name	Method	Units	Castrol GTX Diesel 15W-40
Density @ 20C, Relative	ASTM D4052	g/ml	0.882
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.52
Viscosity, CCS -20C	ASTM D5293	mPa.s (cP)	6120
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	100.2
Viscosity Index	ASTM D2270	None	137
Ash, Sulphated	ASTM D874	% wt	1.18
Pour Point	ASTM D97	°C	-27

Product Performance Claims

API CH-4/SJ

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX Diesel 15W-40

13 Dec 2011

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa

+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)

www.castrol.co.za