



## LHM+

Mineral hydraulic fluid

### Description

Castrol LHM + is specifically designed for use in powered hydraulic systems, which generally incorporate a pump driving such components as brake actuation, suspension levelling and power steering. Castrol LHM + is a mineral based fluid specially designed for Citroen hydraulic systems with green reservoirs.

### Application

Castrol LHM+ is formulated using thermally stable mineral oils and additives. It has a wide working temperature range of between -40°C to 100°C

Castrol LHM+ contains corrosion inhibitors and antioxidants providing excellent corrosion protection to all metals components and compatibility to all elastomeric components found within automotive powered hydraulic systems recommending this type fluid.

This product has a very high viscosity index (VI) which means the products viscosity changes less with temperature than many other similar products. It is very shear stable ensuring the unique viscometric properties of the fluid are maintained for longer throughout its service life.

Castrol LHM+ has excellent lubricity performance ensuring reduced wear and longer component life.

### Conditions of Use

Castrol LHM+ is compatible with other older LHM fluids but for optimum performance should not be mixed with other grades. A complete change of fluid is recommended .

Castrol LHM+ is not compatible with synthetic brake fluids DOT3, 4,5. 1 and LHS 2 type fluids.

## Typical Characteristics

Name	Method	Units	Castrol LHM+
Flash Point	NFT 60-103	°C	110
Density @ 20C	IP 160	g/ml	0.844
Viscosity, Kinematic -40C	IP 71	mm <sup>2</sup> /s	1150
Viscosity, Kinematic 40C	IP 71	mm <sup>2</sup> /s	20
Viscosity, Kinematic 100C	IP 71	mm <sup>2</sup> /s	6.2
Viscosity Index	IP 226	None	320
Pour Point	ISO 3016	°C	-50
Appearance	Visual	-	Fluorescent green clear mobile liquid

## Product Performance Claims

ISO 7308

Compliance to Citroen and Peugeot PSA B71 2710

LHM+  
25 May 2011  
Castrol, LHM+ and the Castrol logo are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa  
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)  
[www.castrol.co.za](http://www.castrol.co.za)