



Castrol Magnatec Professional A3 5W-40

Instant protection from the moment you turn the key

Description

Castrol Magnatec Professional's intelligent molecules cling like a magnet, dramatically reducing* engine wear. Micro filtered and with its signature green colour it's your guarantee of Professional quality.

Up to 75% of engine wear happens while your engine warms up. When the engine stops, oils drain off critical engine parts, however Castrol Magnatec Professional's intelligent molecules don't. They cling to the engine like a magnet providing an extra layer of protection; ready to protect from the moment you turn the key.

Castrol Magnatec Professional, an SAE 5W-40 engine oil, has been specially engineered to deliver outstanding wear protection in today's modern engines.

Castrol Magnatec Professional. Instant protection from the moment you turn the key.

** As tested against the industry Sequence IVA wear test*

Application

Castrol Magnatec Professional A3 5W-40 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA A3/B4, A3/B3, API SN/CF or earlier specification 5W-40 lubricant.

Castrol Magnatec Professional A3 5W-40 is approved for use in vehicles from a wide range of manufacturers, please refer to the specifications section and your vehicle handbook.

Advantages

Castrol Magnatec Professional's Intelligent Molecules:

- Cling to critical engine parts when the oil drains down.
- Cling to your engine forming an extra layer that protects from the moment you turn the key.
- Bond to metal surfaces to make engine parts more resistant to wear.
- Provide continuous protection for all driving conditions, styles and temperatures.

Castrol Magnatec Professional A3 5W-40 delivers superior performance under extreme cold start up conditions.

Typical Characteristics

| Name | Method | Units | Magnatec Professional A3 5W-40 |
|---------------------------|------------|--------------------|--------------------------------|
| Density @ 15C | ASTM D1298 | g/ml | 0.853 |
| Viscosity, Kinematic 100C | ASTM D445 | mm ² /s | 13.9 |
| Viscosity, CCS -30C (5W) | ASTM D5293 | mPa.s (cP) | 6180 |
| Viscosity, Kinematic 40C | ASTM D445 | mm ² /s | 84 |
| Viscosity Index | ASTM D2270 | None | 170 |
| Pour Point | ASTM D97 | °C | -39 |
| Flash Point, PMCC | ASTM D93 | °C | 210 |
| Ash, Sulphated | ASTM D874 | % wt | 1.18 |

Product Performance Claims

ACEA A3/B3, A3/B4
API SN/CF
BMW Longlife-01
MB-Approval 229.3/ 229.5
Renault RN 0700 / RN 0710
VW 502 00/ 505 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Magnatec Professional A3 5W-40
18 Oct 2011
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)
www.castrol.co.za