



Castrol Magnatec Professional A3 5W-30

Instant protection from the moment you turn the key.

Description

Castrol Magnatec Professional's intelligent molecules cling like a magnet, dramatically reducing* engine wear. Micro filtered and with its signature green colour it's your guarantee of Professional quality.

Up to 75% of engine wear happens while your engine warms up. When the engine stops, oils drain off critical engine parts, however Castrol Magnatec Professional's intelligent molecules don't. They cling to the engine like a magnet providing an extra layer of protection; ready to protect from the moment you turn the key.

Castrol Magnatec Professional, an SAE 5W-30 engine oil, has been specially engineered to deliver outstanding wear protection in today's modern engines.

Castrol Magnatec Professional. Instant protection from the moment you turn the key.

** As tested against the industry Sequence IVA wear test.*

Application

Castrol Magnatec Professional A3 5W-30 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA A3/B4, API SL/CF or earlier specification 5W-30 lubricant.

Castrol Magnatec Professional A3 5W-30 is approved for use in vehicles from a wide range of manufacturers, please refer to the specifications section and your vehicle handbook.

Advantages

Castrol Magnatec Professional's Intelligent Molecules:

- Cling to critical engine parts when the oil drains down.
- Cling to your engine forming an extra layer that protects from the moment you turn the key.
- Bond to metal surfaces to make engine parts more resistant to wear.
- Provide continuous protection for all driving conditions, styles and temperatures.

Castrol Magnatec Professional A3 5W-30 also delivers superior performance under extreme cold start up conditions.

Typical Characteristics

Name	Method	Units	Castrol Magnatec Professional A3 5W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.85
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	11.4
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	5860
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	66
Viscosity Index	ASTM D2270	None	169
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	200
Ash, Sulphated	ASTM D874	% wt	1.22

Product Performance Claims

ACEA A3/B3, A3/B4
API SL/CF
BMW Longlife 01
Meets Fiat 9.55535-G1
GM LL-A-025, LL-B-025
MB-Approval 229.3
Renault RN 0700
VW 502 00/ 505 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Magnatec Professional A3 5W-30

01 Jun 2011

Castrol, Magnatec Professional A3 5W-30 and the Castrol logo are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa

+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)

www.castrol.co.za