



Tection Monograde 30

Monograde protection for commercial vehicles and equipment

Description

Castrol Tection Monograde is a diesel engine oil available in SAE 10W, 30, 40 & 50 viscosities.

Application

The primary application of Castrol Tection Monograde 30 is in diesel engines, hydraulic systems and transmissions that specify the use of a monograde diesel engine oil.

Advantages

Castrol Tection Monograde 30 provides excellent protection in applications where a monograde diesel engine oil is required.

User benefits include:

- Protection against wear and deposits. Castrol Tection Monograde 30 is formulated to reduce many types of wear and also reduce the build-up of deposits, so maintenance costs are controlled and unscheduled downtime is prevented.
- Can be used in hydraulic and transmission systems that specify use of a monograde engine oil.

Typical Characteristics

Name	Method	Units	Tection Monograde 30
Product Code			14533
Density @ 20C, Relative	ASTM D4052	kg/l	0.891
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	11.87
Flash Point, COC	ASTM D92	°C	232
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	106.7
Viscosity Index	ASTM D2270	None	100
Ash, Sulphated	ASTM D874	% wt	0.492
Total Base Number, TBN	ASTM D2896	mg KOH/g	8.6
Pour Point	ASTM D97	°C	-21

Product Performance Claims

SAE 30
ACEA E1
API CF
MB-Approval 228.0

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Tecton Monograde 30

10 Feb 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)
www.castrol.co.za