



## Transmax Dex VI

Automatic Transmission Fluid

### Description

Castrol Transmax Dex VI is approved for use in all General Motors automatic transmissions. It is licensed against Dexron® VI which supersedes all previous Dexron® specifications for General Motors Holden applications.

### Advantages

- Low viscosity formulation provides fuel economy benefits compared with fluids formulated to meet Dexron® IIIH or earlier specifications.
- Premium synthetic formulation gives outstanding oxidative resistance extending transmission life.
- Enhanced friction durability improves shifting performance.

### Typical Characteristics

Name	Method	Units	Transmax Dex VI
Appearance	Visual	-	Red , Clear and Bright
Density @ 15C	ASTM D4052	g/ml	0.846
Pour Point	ASTM D97	°C	-54
Flash Point, COC	ASTM D92	°C	206
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	6.0
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	29.8
Viscosity Index	ASTM D2270	None	151
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	12,400

### Product Performance Claims

GM Dexron VI

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Transmax Dex VI

26 Sep 2011

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa

+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)

[www.castrol.co.za](http://www.castrol.co.za)