



## Castrol Transmax Mercon V

Automatic Transmission Fluid

### Description

Castrol Transmax Mercon® V is certified for use in Ford vehicles requiring Mercon® V or Mercon®. NB: Do not use in applications requiring Mercon® SP or Type F.

### Advantages

- Enhanced friction durability provides superior transmission life and promotes smooth shifting.
- Exceptional thermal protection guards against transmission wear.

### Typical Characteristics

Name	Method	Units	Transmax Mercon V
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	7.4
Pour Point	ASTM D97	°C	-40
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	9800
Viscosity Index	ASTM D2270	None	148
Flash Point, PMCC	ASTM D93	°C	177

### Product Performance Claims

Meets Ford Mercon® V

### Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Transmax Mercon V  
19 Jul 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa  
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)  
www.castrol.co.za