



## CRB Multi 15W-40 CH-4

For Long and healthy engine life

### Description

Castrol CRB Multi 15W-40 CH-4 is a multi-purpose, heavy duty diesel engine oil. It is suitable for use in high speed 4-stroke diesel engines that use a broad range of fuel qualities.

### Application

It is suitable for use in most makes of trucks, buses, LCV and off-highway vehicles and equipment. It is designed for use in high performance, heavy duty diesel engines operating in demanding conditions but can also be used in light commercial diesel and gasoline engines, making it an ideal choice for mixed fleet operations.

The product meets the requirements of API SJ performance and can be used in petrol applications requiring API SJ performance or lower.

### Advantages

During its working life, your engine faces challenges from combustion by-products that can form deposits, and thicken the oil. Castrol CRB Multi combats these issues in two ways:

1. It contains cleaning agents which displace particles that may otherwise build up on your engine surfaces reducing deposits.
2. It also contains anti-oxidants which disrupt the chemical reactions that can lead to oil thickening.

Castrol CRB Multi provides effective piston deposit control and maintains its viscosity to encourage long and healthy engine life.

### Typical Characteristics

Name	Method	Units	CRB Multi 15W-40 CH-4
Density @ 15C	ASTM D4052	g/ml	0.88
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	14.5
Viscosity, CCS -20C (15W)	ASTM D5293	mPa.s (cP)	6300
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	110
Viscosity Index	ASTM D2270	None	130
Ash, Sulphated	ASTM D874	% wt	1.5
Total Base Number, TBN	ASTM D2896	mg KOH/g	11
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	202

## Product Performance Claims

API CH-4/SJ

### Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

CRB Multi 15W-40 CH-4

11 Oct 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

199 Oxford Road, Dunkeld, Johannesburg, 2196, South Africa  
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)  
[www.castrol.co.za](http://www.castrol.co.za)