



Radical NF

Antifreeze coolant

Description

Castrol Radical NF is an antifreeze concentrate formulated using monoethylene glycol and selected additives, free from nitrite, amine and phosphate inhibitors. It uses hybrid technology for the modern performance engines of cars and trucks.

This coolant should be used at concentrations of between 33% and 50% dilution with purified water to give optimum corrosion protection and freezing protection between -18°C and -36°C.

Application

Castrol Radical NF has been developed to meet the growing demand from engine and vehicle manufacturers for a higher performance coolant that minimises environmental impact. It provides excellent protection against corrosion, and because it contains no phosphate, the problems of deposits in some modern performance engines are eliminated. In addition to providing excellent corrosion and low temperature protection, the use of the recommended level of antifreeze will significantly reduce the likelihood of wet cylinder liner pitting due to "cavitation erosion". Cavitation erosion is caused by the implosion of air bubbles present in the coolant, which are attracted to the liner outer surface. These bubbles implode, resulting in the removal of minute amounts of liner material, this, if allowed to continue unchecked, will result in liner porosity and severe engine damage.

- Protects for up to 3 years
- Excellent low temperature protection
- Provides excellent protection against corrosion
- Efficient lubrication of water pumps
- Compatible with conventional seal and hose materials used in engine cooling systems
- Contains bittering agent.
- Has many OEM approvals

In the majority of cases, coolants are not compatible and should not be mixed with other coolants unless directed by the equipment manufacturer. If using Castrol Radical NF for the first time, ensure that the cooling system has been adequately flushed with clean water.

Typical Characteristics

Name	Method	Units	Castrol Radicool NF
Density @ 20C, Relative	IP 160	g/ml	1.122
Water	ASTM D1123	% wt	3.5 max
Boiling Point of Engine Coolants	ASTM D1120	°C	174
Reserve Alkalinity	ASTM D1121	ml 0.1N HCl	15
Appearance	Visual	-	Blue/green
pH, Engine Coolants / Antirusts	ASTM D1287	-	7.3

Product Performance Claims

ASTM D3306, ASTM D4985
BS - BS6580:2010
JASO JIS K2234
MAN 324 Typ NF
MB-Approval 325.0
MTU MTL 5048
VW TL-774C (G11)
BMW approval for all models
Deutz - DQC CA-14

Storage

Castrol Radicool NF shall be stored in air tight containers at a maximum temperature of 30°C. In warm climates containers should not be stored outside in direct sunlight. It can be stored in mild steel lacquer lined containers. Galvanised containers and handling equipment should not be used.

Radicool NF
20 Apr 2018
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)
www.castrol.co.za